



亞泰金屬工業股份有限公司
ASIA METAL INDUSTRIES, INC.

軟性銅箔基板塗貼機

FLEXIBLE COPPER CLAD LAMINATE (FCCL) COATING MACHINE



規格 / SPECIFICATION

基材	Base Material	▶	PI 聚醯亞胺 (12~175 μ m)、銅箔Copper Foil (9~36 μ m)
機速	Mechanical Speed	▶	1.5~20 M/min
塗佈方式	Coating Method	▶	Slot Die
塗佈精度	Coating Accuracy	▶	(dry) 3 layer : 10~30 μ m \pm 1 μ m、2 layer : 12~20 μ m \pm 1 μ m
加熱方式	Heating Method	▶	熱媒油 / Hot Oil 電熱 / Electric Heating 瓦斯 / Gas
烘箱型式	Oven Type	▶	空浮式(+ 底部導輾支撐) Air floatation type (+ guide roller support at the bottom)
烘箱溫度	Oven Temperature	▶	Max. 200 $^{\circ}$ C
乾燥方式	Drying Method	▶	熱風 / Hot Air
貼合功能	Laminating Function	▶	貼合溫度 / Laminator temperature ▶ Max. 150 $^{\circ}$ C
		▶	有效區域溫度 / Available Area Temperature ▶ \pm 1 $^{\circ}$ C
潔淨度	Cleanness	▶	Class 1000

32663 台灣桃園市楊梅區民富路2段199巷16號
NO. 16, Lane 199, Section 2, Minfu Road, Yangmei District,
Taoyuan City 32663, Taiwan

+886-3-472-7111 ext. 251 / 469
+886-3-472-3418
www.asiametal.com.tw



網站連結



型錄下載