



亞泰金屬工業股份有限公司
ASIA METAL INDUSTRIES, INC.

複合材料含浸機

CCL VERTICAL TREATER



規格 / SPECIFICATION

基材 Base Material	▶	玻璃纖維布 1010~7628 / Glass fabric 1010~7628
機速 Mechanical Speed	▶	5~30 M/min
塗佈方式 Coating Method	▶	含浸處理機：預浸裝置、含浸裝置、計量裝置 Saturator：Prewet unit, Saturator unit, Metering unit
加熱方式 Heating Method	▶	1. 熱媒油加熱 / Hot oil heating 2. 電加熱 / Electric heating
烘箱溫度 Oven Temperature	▶	熱媒油加熱，最高 250°C / Hot oil heating Max. 250°C 電加熱板，最高 500°C / Electric heating Max. 500°C
烘箱高度 Height of Dryer	▶	20 呎 / 20' 30 呎 / 30' 40 呎 / 40' 50 呎 / 50'

📍 32663 台灣桃園市楊梅區民富路2段199巷16號
NO. 16, Lane 199, Section 2, Minfu Road, Yangmei District,
Taoyuan City 32663, Taiwan

☎ +886-3-472-7111 ext. 251 / 469
☎ +886-3-472-3418
www.asiametal.com.tw



網站連結



型錄下載